



Technical Data Sheet	Liquid Paint Related
TEK-CLEAN Final Prep Surface Cleaner	36-702
For Professional Use	Rev 2.21.26

Product Description

TEK-CLEAN Final Prep Surface Cleaner is a Fast drying pre-paint solvent cleaner that removes sanding sludge, dust, silicones, light oils, grease, smudges and fingerprints. Use on all metals, fully cured refinish and OEM finishes, sanded substrates, and fully cured primers and or sealers prior to refinish operations. Completely dry surfaces with a *clean dry lint free cloth, do not allow to air dry.

Always refer to **Safety Data Sheet** for complete safety information.

General Information



READ ALL INSTRUCTIONS AND SAFETY PROCEEDURES PRIOR TO USING!
IMPORTANT: This Product contains hazardous materials



Proper Protective equipment should be used at all times. Please consult product label as well as Safety Data Sheet for complete safe handling procedures .
Use suitable protective equipment.

Compatible Prepared Substrates

Fully cured refinish and OEM finishes, sanded substrates, primers and fully cured sealers.

Caution: Not intended for use on unprimed plastic or fiberglass substrates due to the possibility of static buildup, this can cause flash fire.

Surface Preparation

Prior to sanding clean all surfaces to remove wax and grease with VTK 36-700 Wax and Grease Remover or VTK 36-707 Zero VOC Waterborne Surface Cleaner.

Mixing

This product is Ready To Use. **No mixing required**



Technical Data Sheet	Liquid Paint Related
TEK-CLEAN Final Prep Surface Cleaner	36-702
For Professional Use	Rev 2.21.26

Application



- Saturate a clean soft *cloth with 36-702 TEK CLEAN Final Prep Surface Cleaner
- Wipe the areas to be cleaned to dissolve and remove contaminants
- Follow Immediately with a clean dry towel.



TEK-TIP

- Completely wipe dry, **do not allow to air dry** as contaminants can be left behind. If surface air-dries, repeat process.
- * **For best results** we recommend using **VIETEK 43-135, 155, or 156 Highly absorbent lint-free TEK-PRO Wipers**

Technical Data

VIETEK 36-702 TEK-CLEAN Final Prep Surface Cleaner

Compliance: Always check local Air Quality Regulations to assure compliance and approved application methods

Storage: Store in a cool/dry location

Shelf life: in the original unopened container up to 60 months @70°F.

Close Cap when not in use to prevent evaporation and maintain product properties and performance.



Physical Values

All Values Ready To Use

Max. **VOC** (Regulatory) : 727 g/L (6.1 lbs./gal)

Max. **VOC** (Applied, Actual) : 727 g/L (6.1 lbs./gal)

Avg. Gal. Wt.: 727 g/L (6.07 lbs./gal)

Avg. Wt.% Volatiles: 100.0%

Avg. Wt.% Exempt Solvent: 0.0%

Avg. Wt.% Water: 0.0%

Avg. Vol.% Exempt Solvent: 0.0%

Avg. Vol.% Water: 0.0%

Flash Point: See SDS

Manufactured in The USA for:
National Coatings and Supplies 4900
Falls of Neuse Rd, Ste. 150 Raleigh, NC
27609
www.ncssi.com
(866) 529-1682



See our full VIETEK line at:
www.VIETEK.com
For additional information
scan our QR code.